2013 HINIKER SNOWPLOW SELECTION GUIDE																	
MINIMUM FRONT GROSS AXLE WEIGHT RATING (FGAWR) <sup>1</sup> & ELECTRICAL HEAD LIGHT ADAPTER REQUIRED BY MODEL																	
Ram 2013			Mid-Size Poly		Metal Straight			Poly Scoop		Poly C		Poly Straight		Poly V		Poly Straight	
			702 7'	752 7 1/2'	2753 7 1/2'	2803 8'	2853 8 1/2'	* 6801 8'	* 6901 9'	* 8802 8'	* 8902 9'	* 7802 8'	* 7902 9'	* 9851 * 9860 8 1/2'	* 9951 * 9960 9 1/2'	* 10331 10'	* 10332 10'
Ram 4500 & 5500 ST Model Chassis Cab 4 x 2 & 4 x 4 Mount Kit p/n 25013305 * 25013306 <b>QH2</b>		Head light adapter p/n 38813068 for H13/9008 bulb(s). Head light adapter p/n 38813046 for Projector Head Lights.															
Reg Cab & Crew Cab DRW	144.5" 168.5" 173.5" 192.5" 197.5" 204.5" W.B.	6.7L Diesel					7000		7000		7000		7000		7000	7000	7000

The truck, attached equipment and ballast should not exceed the front axle or total vehicle rating.

Notes:

SRW=Single Rear Wheel

DRW=Dual Rear Wheel

WB=Wheel Base

Ballast may be required for snowplow applications.

Ram recommends trucks be equipped with the optional snowplow prep package where available.

## A Full Line of High Performance Snowplows and Spreaders

















<sup>\*</sup> Quick Hitch 2 Plows and Mounts