

HINIKER SNOWPLOW SELECTION GUIDE

MINIMUM FRONT GROSS AXLE WEIGHT RATING (FGAWR)¹ & ELECTRICAL ADAPTER REQUIRED BY MODEL

		Mid-Size Poly		Metal Straight Blade			Poly Scoop Blades		Poly C Blades		Poly Straight Blades		Poly V Blades		10' Blades	
		7'	7 1/2'	7 1/2'	8'	8 1/2'	8'	9'	8'	9'	8'	9'	8 1/2'	9 1/2'	10'	10'
Ford® F550 2016	Past Plow Models	700-702	750-752	2752-2753	2802-2803	2852-2854	6800 * 6801-6813	6900 * 6901-6913	8801 * 8802-8803	8901 * 8902-8903	7801 * 7802-7813	7901 * 7902-7913	9850 * 9851-9862	9950 * 9951-9962	*9610	10331 * 10333
	Current Plow Models	703	753	2754	2804	2854	* 6814	* 6914	* 8804	* 8904	* 7814	* 7914	* 9863 9585	* 9963 9595	9710	-
F550 4x4 Mount Kit p/n 25013120 QH1 or 25012862 QH2		Head light adapter p/n 38813068 for H13/9008 bulb(s) with CPC or HTBX Harness Headlight adapter p/n 38813038 for H6054 bulb(s) with CPC or HTBX Harness Headlight adapter p/n 38813112 for HB3 (9005)/ H11 bulb(s) with CPC or HTBX Harness														
Regular Cab Chassis	6.8 L Gas				4800	4800	5200	5200	5200	5200	5200	5200	5200	5200	5200	5200
Regular Cab Chassis	6.7L Diesel				5600	5600	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
Super Cab Chassis	6.8 L Gas				5200	5200	5200	5600	5200	5600	5200	5600	5200	5600	5600	5600
Super Cab Chassis	6.7L Diesel				6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
Crew Cab Chassis	6.8 L Gas				5600	5600	5600	5600	5600	5600	5600	5600	5600	5600	5600	5600
Crew Cab Chassis	6.7L Diesel				6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500	6500

¹ The truck, attached equipment and ballast should not exceed the front axle or total vehicle rating. Ballast may be required for some snowplow applications.

Before purchasing, installing or using your Hiniker snowplow, ensure your vehicle is equipped with all the vehicle manufacturer's and Hiniker's required options for snowplowing.

* Quick Hitch 2 Plow and Mounts

HTBX Harness needs to be paired with 38828014 universal truck harness. 2023 and later plows need to be ordered with either LED or Halogen light kits.

