

HINIKER SNOWPLOW SELECTION GUIDE
MINIMUM FRONT GROSS AXLE WEIGHT RATING (FGAWR)¹ & ELECTRICAL ADAPTER REQUIRED BY MODEL

		Mid-Size Poly		Metal Straight Blade			Poly Scoop Blades		Poly C Blades		Poly Straight Blades		Poly V Blades		10' Blades	
		7'	7 1/2'	7 1/2'	8'	8 1/2'	8'	9'	8'	9'	8'	9'	8 1/2'	9 1/2'	10'	10'
Ford® F150 2014	Past Plow Models	700-702	750-752	2752-2753	2802-2803	2852-2854	6800-6813	6900-6913	8801-8803	8901-8903	7801-7813	7901-7913	9850-9862	9950-9962	*9610	10331 * 10333
	Current Plow Models	703	753	2754	2804	2854	* 6814	* 6914	* 8804	* 8904	* 7814	* 7914	* 9863-9585	* 9963-9595	9710	-
F-150 4x4 Pickup <i>Only XLT, FX, LARIAT and PLATIUM Trim Levels</i> Mount Kit p/n 25012702		Head light adapter p/n 38813079 for H13/9008 bulb(s) with Sure Seal Connector Head light adapter p/n 38813068 for H13/9008 bulb(s) with CPC or HTBX Harness REQUIRED: A snowplow outside air temperature (OAT kit # DL3Z-14K073-A) is available through Ford®. Installation of this kit is required if a snowplow is to be installed. Failure to relocate the OAT sensor will degrade the vehicles ability to maintain automatic interior climate control settings.														
Super Cab 6 3/4' Box	6.2L Gas	4050	4050													
Super Cab 8' Box	6.2L Gas	4050	4050													
Crew Cab 6 3/4' Box	6.2L Gas	4050	4050													

¹ The truck, attached equipment and ballast should not exceed the front axle or total vehicle rating. Ballast may be required for some snowplow applications. Before purchasing, installing or using your Hiniker snowplow, ensure your vehicle is equipped with all the vehicle manufacturer's and Hiniker's required options for snowplowing.
 * Quick Hitch 2 Plow and Mounts
 HTBX Harness needs to be paired with 38828014 universal truck harness. 2023 and later plows need to be ordered with either LED or Halogen light kits.

