



Auger Delivery Spreader

Contact us 800-433-5620
today: hiniker@hiniker.com



Features and Benefits:

- Dual 12-volt motors independently power the auger and spinner
- Standard steel hopper screens have 2 3/8" square openings, 1/4" rods.
- Standard electric hopper vibrator
- 2.0, 2.75, 4 cubic yard level capacity

Conveyor Delivery Spreader



Features and Benefits:

- Available in either gas or electric
- Corrosion-resistant stainless steel construction
- In-cab electric control of starter, throttle, and clutch functions



Poly Tailgate Spreader



Features and Benefits:

- One of a kind “No-Dribble” bubble auger design, means the flow stops when the auger stops.
- High-quality hoppers in 6 and 10 cubic foot capacities.
- Superior design, construction, and components in a contractor-duty spreader.

Specifications

	775	955	975
Auger Delivery			
Level Capacity	2.00 Cubic Yards	2.75 Cubic Yards	4.00 Cubic Yards
Length	100" Overall 91" Hopper	122" Overall 111" Hopper	122" Overall 111" Hopper
Top Width	51"	51"	51"
Conveyor Delivery			
Level Capacity	1.80 Cubic Yards	1.80 Cubic Yards	
Length	115" Overall 96" Hopper	115" Overall 96" Hopper	
Top Width	50.5"	50.5"	
Mass Application Rate	5 cu. ft./min	7.3 cu. ft./min	
Poly Tailgate			
Level Capacity	6 Cubic Foot	10 Cubic Foot	
Net Weight	126 lb.	148 lb.	